



ANLY RELAY



COIL DATA



AC				DC			
Nominal Voltage (V 50/60Hz)	Resistance Tol.±10% (Ohms DC)	Maximum Pick up Voltage(V)	Minimum Drop Out Voltage(V)	Nominal Voltage (VDC)	Resistance Tol.±10% (Ohms DC)	Maximum Pick up Voltage(V)	Minimum Drop Out Voltage(V)
6	10	4.8	1.8	6	40	4.5	0.6
12	45	9.6	3.6	12	160	9.0	1.2
24	160	19.2	7.2	24	650	18.0	2.4
48	670	38.4	14.4	48	2,600	36.0	4.8
100/110	3,900	88.0	33.0	110	11,000	82.5	11.0
220/240	16,000	176.0	66.0				

GENERAL DATA

Insulation Resistance	100 Megohms min. at 500 VDC
Breakdown Voltage	500 Vrms, 50/60 Hz between contact, 1,500 Vrms, 50/60Hz between all elements
Contact Material	Silver-Cadmium Oxide as standard
Contact Resistance	50 milliohms max. (Initial value)
Coil Data	See chart. (at 25°C)
Max. Allowable Voltage	110% of nominal
Min. Drop-out Voltage	10% of nominal (DC), 30% of nominal (AC)
Pick-up Time	15 msec max.
Drop-up Time	15 msec max.
Temperature Range	-40°C~+60°C
Expected Life	Mechanical -10,000,000 operations min. (at 18,000 operations/hr) Electrical - 100,000 operations min. (at 1,800 operations/hr)



ONLY RELAY

RELAY TYPE	AHL2 / AHL2N*	
		
Connection Diagram		
Outline : L × W × H (mm)	28 × 21.5 × 35	
Contact Arrangement	2PDT	
Contact Rating	Resistive Load(Cos φ =1)	AC 240V/DC 30V 12A
	Inductive Load(Cos φ =0.4)	AC 240V 5A
Coil Voltage	DC(V) 6, 12, 24, 48, 110 AC(V) 6, 12, 24, 48, 100/110, 220/240	
Coil Power (Nominal)	AC 1.2VA DC 0.9~1.1W	
Insulation Resistance	DC 500V 100MΩ min.	
Approximate Weight	37g	
Recongized Safety Standard	UL, C-UL, CE	
Dimensions(mm)		
Relay Socket	PTF-08AE	
Hold-down Clip	PYC-A1	
		

*TYPE AHC2N, AHC4N and AHL2N have LED indicator.

ONLY ELECTRONICS CO., LTD.

<http://www.only.com.tw>

NO. AHCL-K-A